WORK LAMP

WL 75W 50W
WLA 30W

Work Lamp is specially designed for multi-task functions. It is IP65 rated suitable for both Indoor and outdoor application such as building wall washing, medium billboard, walkways as well as landmarks. With its high lighting efficacy,the safety of working in construction sites will be ensured.

Product Overview

Features

- Solid die-cast aluminum housing
- UV rated powder paint coating
- Rotatable bracket made of stainless steel
- System efficacy up to 168 lm/W (Ra > 70)
- IK07 impact rating
- IP65 rated for outdoor applications

Specifications

- Power Consumption : 75 W / 50 W / 30 W
- Input Voltage : AC 90-264 V
- Frequency : 50/60 Hz
- Operation Temp. : -30°C to +45°C
- LED Lifetime (L_{70}) : 60,000 hours

Dimensions [Unit : mm]

WL 75W Weight : 2.7 Kg



WL 50W Weight : 2.7 Kg



WLA 30W Weight : 1.1 Kg



Photometric [Figures are shown in steady stage]

WL / Beam Angle **120°**



M	50W (5000K, C7)	75W (5000K, C7)
1	1931 LUX	3394 LUX
2	483 LUX	849 LUX
3	215 LUX	377 LUX

WLA / Beam Angle **120°**



M	30W (5000K, C7)
1	1140 LUX
2	285 LUX
3	127 LUX

Ordering Information

Product Name	Wattage (W)	CCT (K)	Beam Angle (°)	CRI	Light Output Steady Stage (lm)	Light Output Cold Stage (lm)
WLA-30S-V-csil-C30WDA2C7	30	5000	120	>70	4250	4700
WL-50K0-V-c-C30WDA2C7	50	5000	120	>70	7200	8000
WL-75S-V-c-C30WDA2C7	75	5000	120	>70	11350	12600

** Other CCT options : 3000K, 4000K, 6500K.*

All technical data are subject to change without notification.